



## **C-19P**

An excellent and affordable 19" display for home and office environments where quality, reliability and price are important considerations.

The valuable C-19P delivers the high image clarity and outstanding display performance that is well suited for the demands of modern office and home applications. Featuring 1,000:1 typical contrast ratio and built-in speakers, the slim modern design and convenient VESA compatible wall mounts make the C-19P a perfect value choice for home and office environments.

- > LED-backlit technology
- > Slim and sleek design
- > Fast 3ms response time
- > Crisp 1,000:1 typical contrast ratio
- > Built-in speakers (3W x 2)
- > Tilt from -5 ° to +20 ° for optimal viewing
- > Kensington $^{\circ}$  security socket
- > VESA standard wall mount
- > WEEE, RoHS, REACH certified

## **C-19P**

Specifications		C-19P
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments  Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD 19.0" (482 mm) SXGA 1280 x 1024 0.294 mm 250cd/m2 (Typical) 1,000:1 (Typical) Hard Coating (3H), Anti-glare treatment 170°/170° (Typical) 16.7M 3ms (GTG)
Frequency (H/V)		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
Input	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
Audio	Audio In Speaker	1 x Stereo audio in for PC (audio jack, 3.5ø) 3W x 2
Power	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 18 W (On) < 0.5 W (Stand-by) < 0.5 W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-5° ~ +20°
Dimensions	Product (W x H x D) Packaging (W x H x D)	422 x 388 x 195 mm (16.6" x 15.3" x 7.7") 478 x 403 x 140 mm (18.8" x 15.9" x 5.5")
Weight	Product Weight Packaged Product Weight	3.9 kg (8.6 lbs) 5.8 kg (12.8 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
Accessories	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5  $^{\circ}$  to +20  $^{\circ}$  for optimal viewing







